



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY **LIST CODE**

THRESHOLD

Standard (50mm)

Low* (15mm)

Ramps (DV174)

DOOR STACKING

Open In

Open Out

DRAINAGE

None

Face

CILL

None

85mm (ETC451)

150mm (ETC457)

190mm (ETC458)

225mm (ETC479)

ADD-ON - 42mm

AW42 DV515

Head

Cill

Left

Right

Trickle Vents

ADD-ON - 20mm

DV559

Head

Cill

Left

Right

HANDLE COLOUR

Chrome

White

Silver

Black

Grey

Hinges Rollers & Top Guides in Black

KIT FORM***

GLAZING

Unglazed

**Glazed

UPGRADE

Planitherm One

ITEM DETAILS

Item	Qty
Width	
Height	

EXTRUSION COLOUR

White Gloss (SA018E) <input type="checkbox"/>		
Grey Matt (RAL 7016) <input type="checkbox"/>	External	Finish
Black Matt (RAL 9005) <input type="checkbox"/>	Internal	Finish

Location

NOTES

ITEM STYLE

Min Sash Width 700mm
Max Sash Width 1200mm
Max Sash Height 2500mm

TERMS AND CONDITIONS

Overall sizes to include cills and add-ons (transom, mullion and midrail sizes are excluding cills and add-ons). Once the frames have been assembled, re-works, cut-downs or any alterations will not be possible. Please check the order details carefully. Open In doors will have an DBV1-12 'D' handle above each Debar handle. Black as standard. (Excluding PAS24). Bi-fold outer frames, cills and add-ons exceeding 5000mm in width may require splitting. If not specified, we will split optimally. *Low Threshold has no weathering guarantee and is not recommended for external use. DV171 is used for Open In, DV271 for Open Out. **Standard bifold glazing is 28mm Planitherm Total +, Argon, Black Thermobar, Toughened. ***Doors exceeding 4000 in width or 2400 in height will be supplied in kit form. Full terms and conditions can be found on our website www.a-w-s.co.uk.