



Customer		
Customer Address	Delivery Address (if different)	Page of
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY

LIST CODE

OUTER FRAME

VG510 Standard (99mm)

Cill

- None
- 150mm (ETC457)
- 190mm (ETC458)
- 225mm (ETC479)
- Drainage (VG556)

Add-on

- 42mm (VG558)
 - Head
 - Cill
 - Left
 - Right
- Trickle Vents?

VG511 Upstand (116mm)

Cill

- None
- 190mm (ETC458)
- 225mm (ETC479)

Add-on

- 42mm (VG572)
 - Head
 - Cill
 - Left
 - Right
- Trickle Vents?

INTERLOCKS

Standard 83mm

- VG532 Reinforced In
- VG532 Reinforced Out

Slim 35mm

- VG539 Reinforced Out

HANDLE TYPE/COLOUR

D Handle

- Inside Only/Half Cylinder

Lever Handle

- Inside Only/Half Cylinder
- Inside Lever/Fingerpull Out

No External Locking

Colour

- White
- Silver Anodised
- Black

PREMIUM HANDLES

Grey D Handle

Pole Handle (s/steel)

- Both Sides
- Pole In/Fingerpull Out
- Half Cylinder Inside

EXTRUSION COLOUR








External	Finish
Internal	Finish
White Gloss (SA018E) <input type="checkbox"/>	
Grey Matt (RAL 7016) <input type="checkbox"/>	
Black Matt (RAL 9005) <input type="checkbox"/>	

WIND LOADING

MINIMUM 800PA

Post Code	Altitude (metres)
Distance To Sea (miles)	
Exposed Location?	
Building Height (metres)	
PA	lx

ITEM DETAILS

Item	Qty	
Location		 <input type="checkbox"/>
Width		 <input type="checkbox"/>
Height		 <input type="checkbox"/>
Assembled <input type="checkbox"/> Kit Form <input type="checkbox"/>		 <input type="checkbox"/>
		 <input type="checkbox"/>
		 <input type="checkbox"/>
		 <input type="checkbox"/>

GLAZING

(28mm GLAZING STANDARD)

Notes...

Planitherm Total + Argon, Thermobar Unglazed Other

TERMS AND CONDITIONS

Overall sizes to include cills and add-ons (transom, mullion and midrail sizes are excluding cills and add-ons). Interlocks will be specified to meet wind loading requirements, please see the attached data sheet for further details. Patio sashes slide on the inside as standard. All patios are faced drained and must meet a minimum barrier rating of 800 PA. Patio widths over 3000mm will be made in kit form as standard. Patio outer frames exceeding 5000mm in width may require splitting. If not specified on the survey, we will split optimally. Maximum sash height is 2500mm but must not exceed 250kg. All sizes should be referred to in millimetres. Glass units will be toughened as required for building regulations where necessary. Full terms and conditions can be found on our website www.a-w-s.co.uk. Doc Q comes glazed (Lami in/Tough Out) and a high security cylinder.