

**SHOPLINE SURVEY**

Invoice No  Page  of



Customer   
 Address   
 County  Post Code

Goods £  .   
 VAT £  .   
 Total £  .

Tel No  Contact   
 Fax No  Job Ref

Order Date  /  /   
 Order Req  /  /

**Door** Production Code

Open In   
 Open Out   
 Full Swing

**Outside View Only**

Overall sizes to include the cill (transom, mullion and midrail sizes are excluding the cill)

**Master Leaf**  
 Left   
 Right

**Extrusion Colour**      **Finish**  
 White Gloss  Single Colour  Gloss  Satin   
 Silver Anodised  Dual Colour  Matt   
 RAL / BS

**Customer Signature**  
 \_\_\_\_\_

**Hooklock**  
 Number of Locks   
 None   
 Full - Key In & Out   
     └ Thumb In / Key Out   
 Half - Key In   
     └ Thumb In

| Item                                       | Qty                  | Location             |
|--|----------------------|----------------------|
| <input type="text"/>                       | <input type="text"/> | <input type="text"/> |
| <b>Frame Width</b> <input type="text"/>    |                      |                      |
| <b>Frame Height</b> <input type="text"/>   |                      |                      |
| <b>Door Width</b> <input type="text"/>     |                      |                      |
| <b>Transom Drop</b> <input type="text"/>   |                      |                      |
| <b>Midrail Height</b> <input type="text"/> |                      |                      |
| <b>Mullion Split</b> <input type="text"/>  |                      |                      |

**Electric Strike \***  
 12 Volt  24 Volt   
 AC  DC   
 Fail Safe  Fail Secure

Supplied with internal thumb turn & external key override

**Overhead Closer**  
 Hold Open   
 Non-Hold Open

**Handle**  
 None   
 Fixed Pad   
     └ White   
     └ SA   
     └ Black   
     └ Powder Coated

**Notes:**  
 \* Upgraded latch

All items meet the following specification: **800 PA**

**Wind Loading**  
 Post Code

**Premium Handles**  
 D Handle Specify Colour in Notes   
     └ 250mm   
     └ 350mm   
 Pole (SSS In and Out - Blu Perf)   
     └ 600mm   
     └ 1200mm   
     └ 1800mm   
 Other

**Distance to Sea**  
 0 - 6.5 Miles   
 6.5 - 32 Miles   
 32 + Miles   
**Location**  
 Sheltered   
 Exposed   
**Building Height**  
 0 - 3 Metres   
 3 - 6 Metres   
 6 - 10 Metres   
 10 - 15 Metres   
**Altitude**

**Panic Exit**  
 Single / Master Leaf   
 Slave Leaf   
 Paddle Handle   
 Ext. Access Key & Fixed Pad

**Cill**  
 None   
 SH057 152mm

**Threshold**  
 SH410 Double Ramp   
 SH413 Single Ramp

**Glazing**  
 Single Glazed Specify in notes   
 Double Glazed

**Glass**  
 Affordable Planitherm Total+   
 Unglazed

**Salesperson**  
 \_\_\_\_\_

(AFF2019SHOP)v1.1

Please note:  
 Commercial pivot doors do not have a weather rating. In exposed areas it is possible that they can be blown open, this can lead to draughts / water ingress. Consideration for additional weathering such as a canopy or porch should be made when carrying out site surveys.