



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY

LIST CODE

OUTER FRAME	
006.1900 - 1 Slider (139mm)	<input type="checkbox"/>
006.1901 - 2 Sliders (139mm)	<input type="checkbox"/>
INTERLOCKS	
Slim - 50mm (006.2230)*	<input type="checkbox"/>
Slim - 65mm (006.1987)*	<input type="checkbox"/>
Standard - 94mm (006.1986)	<input type="checkbox"/>
REINFORCING (50mm Only)	
0090/0091 In (30mm Only)	<input type="checkbox"/>
Out (30mm Only)	<input type="checkbox"/>
Both Sides (60mm)	<input type="checkbox"/>
0092/0093 In (50mm Only)	<input type="checkbox"/>
Out (50mm Only)	<input type="checkbox"/>
Both Sides (100mm)	<input type="checkbox"/>
REINFORCING (65mm & 94mm)	
3097/1096 In (37mm)	<input type="checkbox"/>
Out (37mm)	<input type="checkbox"/>
Both Sides (74mm)	<input type="checkbox"/>
3099/1097 In (60mm)	<input type="checkbox"/>
Out (60mm)	<input type="checkbox"/>
Both Sides (120mm)	<input type="checkbox"/>
3099/1098 In (60mm)	<input type="checkbox"/>
Out (60mm)	<input type="checkbox"/>
Both Sides (120mm)	<input type="checkbox"/>
ADD ON'S - 39mm (015.0183)	
Head	<input type="checkbox"/>
Cill	<input type="checkbox"/>
Left	<input type="checkbox"/>
Right	<input type="checkbox"/>
Trickle Vents	<input type="checkbox"/>
FIXING LUGS (056.6020)	
THRESHOLD (Supplied As Standard)	<input type="checkbox"/>
DO NOT FIX THROUGH THE THRESHOLD	
CILL PRESSING	
DO NOT FIX THROUGH THE THRESHOLD	
RP110 110 x 36 <input type="checkbox"/>	UTL036 60 x 40 <input type="checkbox"/>
	UTL035 50 x 30 <input type="checkbox"/>
CILL	
ETC458 190mm Supplied with thermal break tape	<input type="checkbox"/>
No Cill / Pressing Required	<input type="checkbox"/>

EXTRUSION COLOUR	
External	Finish
Internal	Finish
White Gloss <input type="checkbox"/>	
Grey Matt (7016M) <input type="checkbox"/>	
Black Matt (9005) <input type="checkbox"/>	

WIND LOADING		MINIMUM 800PA
Post Code	Altitude (M)	
Distance to Sea (Km)		
Exposed Location?		
Installation Height (M)		
PA	Ix	

ITEM DETAILS			
Item	Qty		
Location			
Width			
Height			
Kit Form <input type="checkbox"/>			
HANDLE TYPE			
Lever Handles			
In & Out (Locking In & Out)	STD <input type="checkbox"/>		
Inside Only (No External Locking)	<input type="checkbox"/>		
Inside Lever/Fingerpull Out (No External Locking)	<input type="checkbox"/>		
HANDLE COLOUR			
White	<input type="checkbox"/>		
Silver (Painted RAL7040)	<input type="checkbox"/>		
Black	<input type="checkbox"/>		
Anthracite Grey	<input type="checkbox"/>		
PREMIUM HANDLE			
Stainless Steel	<input type="checkbox"/>		

*Slim not available on this design
Handles inside only

*Slim not available on this design
Handles inside only

This design uses 006.1900 Outerframe

* Meeting stile = Standard 94mm Sashes

Handles both sides, dependant on windloading (MAX ixx48).
If 030.1099 reinforcing required, then locking is internal only.

OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S
(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)

GLAZING (28mm Standard)	NOTES
Planitherm Total + Argon, Thermobar <input type="checkbox"/>	
Unglazed <input type="checkbox"/>	
Other (Specify in Notes) <input type="checkbox"/>	

TERMS AND CONDITIONS	
<ul style="list-style-type: none"> Interlocks will be specified to meet windloading requirements if reinforcing is required then it will be to the outside as standard. Patio sashes slide on the inside as standard. All patios are faced drained and must meet a minimum barrier rating of 800PA. Patio outer frames exceeding 5000mm in width may require splitting. If not specified on the survey, we will split optimally. Maximum sloping pressing length is 3000mm. Anything exceeding this will be split with a butt strap. Maximum sash height is 2700mm, maximum sash width is 2700mm but must not exceed 300kg. All sizes should be referred to in millimetres. On dual colour orders with white inside, the inside of the patio and the inside of the cill may have a slight variance in colour. 	
All orders are subject to our terms and conditions of sale which are available at: www.a-w-s.co.uk	