



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY

LIST CODE

THRESHOLD

Standard (50mm)

Low* (15mm)

Ramps (EUD03)

DOOR STACKING

Open In

Open Out

ITEM DETAILS

Item	Qty
Width	
Height	

EXTRUSION COLOUR

White Gloss (SA018E) <input type="checkbox"/>		
Grey Matt (RAL 7016) <input type="checkbox"/>	External	Finish
Black Matt (RAL 9005) <input type="checkbox"/>	Internal	Finish

Location **ASSEMBLED***** **KIT FORM*****

SASH

DV26 Round (Std)

DV23 Square

MIDRAIL/TRANSOM

DV30 DV35

49mm 109mm

Available in DV23 sash only

DRAINAGE

Face None

CILL

None

85mm (ETC451)

150mm (ETC457)

190mm (ETC458)

225mm (ETC479)

ADD-ON - 42mm

DV515

Head

Cill

Left

Right

Trickle Vents

ADD-ON - 20mm

Head

Cill

Left

Right

HANDLE COLOUR

Chrome

White

Silver

Black

Grey

PREMIUM HANDLES

Lever on Rose

(on DV23 Sash Only)

Hinges, Rollers & Top Guides in Black

GLAZING

**Glazed

Unglazed

DESIGNS

Door toplight, and side frames must be fabricated separately

Min Sash Width 700mm

Max Sash Width 1200mm

Max Sash Height 2500mm

Restrictor 90°

Not supplied as standard

Required

French Door Handles

Master Left Master Right

Standard

Lever in & out on Master

Internal Shootbolt on slave

Option

Lever handles in & out on both sashes.

(Not available with Low Threshold)

NOTES

OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S
(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)

SIDE FRAME

Fixed

DV18 Round

DV118 Square

Coupler for DV frame

ETC357 - 25mm

SL075 - concealed

Opener - Alitherm 300

ETC304 Outer

ETC328 Sash

ETC357 Coupler

70mm square outer, flat sash, externally glazed with square bead with 25mm coupler

Cill for full height sides

None

As Bifold

Cill for flag side frames

None

85mm (ETC451)

150mm (ETC457)

190mm (ETC458)

225mm (ETC479)

ETC357 & DV515 - when used together the DV515 is split and coupler runs from cill to top of add-on

Couplers are not structural, steel is recommended between bi-folds and toplights.

SL075 Concealed Coupler will run to the underside of Add-On, with Add-On running full width.

TERMS AND CONDITIONS

Once the frames have been assembled, re-works, cut-downs and any alterations will not be possible. Please check the order requirements carefully.

* Low Threshold has no weathering guarantee and is not recommended for external use. DV171 is used for Open In, DV271 for Open Out.

** Standard bifold glazing is 28mm Planitherm Total +, Argon, Black Thermobar, Toughened.

*** Doors exceeding 4000 in width or 2400 in height will be supplied in kit form.

Premium Handles will consist of Stainless Steel Lever on Rose with a separate escutcheon and lockable shootbolt handles.

All orders are subject to our terms and conditions of sale which are available at: www.a-w-s.co.uk