



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY

LIST CODE

OUTER FRAME

Triple Track (210mm) ☐

INTERLOCKS

Standard 94mm (006.1986) ☐

Slim not available on triple track

REINFORCING

3097/1096 Out (37mm) ☐

3099/1097 Out (60mm) ☐

3099/1098 Out (60mm) ☐

39mm ADD ONS (015.0183)

Head ☐

Cill ☐

Left ☐

Right ☐

Trickle Vents ☐

FIXING LUGS (056.6020)

THRESHOLD ☐

(Supplied as standard)

DO NOT FIX THROUGH THE THRESHOLD

NO CILL

NO CILL AVAILABLE ☐

CILL PRESSING

DO NOT FIX THROUGH THE THRESHOLD

RP110 110 x 36 ☐

UTL036 60 x 40 ☐

UTL035 50 x 30 ☐

No Cill/Pressing Required ☐

GLAZING (28mm Standard)

Planitherm ☐

Total + Argon, Thermobar

Unglazed ☐

Other ☐

(Specify in Notes)

EXTRUSION COLOUR

External	Finish
Internal	Finish
White Gloss <input type="checkbox"/>	
Grey Matt (7016M) <input type="checkbox"/>	
Black Matt (9005) <input type="checkbox"/>	

ITEM DETAILS

Item	Qty
Location	
Width	
Height	
Kit Form <input checked="" type="checkbox"/>	

HANDLE TYPE

Lever Handles

In & Out (Locking In & Out) STD ☐

Inside Only (No External Locking) ☐

Inside Lever/Fingerpull Out (No External Locking) ☐

HANDLE COLOUR

White ☐

Silver (Painted RAL7040) ☐

Black ☐

Anthracite Grey ☐

PREMIUM HANDLE

Stainless Steel ☐

WIND LOADING

Post Code

Altitude (M)

Distance to Sea (Km)

Exposed Location?

Installation Height (M)

PA ☐ lx

OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S
(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)

* Meeting stile = Standard 94mm Sashes

Handles both sides, dependant on windloading (MAX ixx48).
If 030.1099 reinforcing required, then locking is internal only.

NOTES

TERMS AND CONDITIONS

- Interlocks will be specified to meet windloading requirements if reinforcing is required then it will be to the outside.
- Patio sashes slide on the inside as standard.
- All patios are faced drained and must meet a minimum barrier rating of 800PA.
- Patio outer frames exceeding 5000mm in width may require splitting. If not specified on the survey, we will split optimally.
- Maximum sloping pressing length is 3000mm. Anything exceeding this will be split with a butt strap.
- Maximum sash height is 2700mm, maximum sash width is 2700mm but must not exceed 300kg.
- All sizes should be referred to in millimetres.
- On dual colour orders with white inside, the inside of the patio and the inside of the cill may have a slight variance in colour.

All orders are subject to our terms and conditions of sale which are available at: www.a-w-s.co.uk