PLEASE CHECK CAREFULLY, ONCE SIGNED OFF WE ARE UNABLE TO ACCEPT AMENDMENTS AFFORDABLE ALUMINIUM SYSTEMS LTD VISOFOLD COEX COMBINATION SURVEY

Customer					_					
Customer Address				Delivery Address (if different) Page						of
									Good	
				VAT						
				Total						
Contact									r Date	
Tel									ery Date	
Fax				Customer Ref						
Email				Sales Contact						
				LIST CODE						
THRESHOLD					_			JODE		
Standard (50mm)	ITEM DETAILS									
Low* (15mm)	Width		<u> </u>	Matt (RAL 7016)		External				Finish
Ramps (EUD03)										
DOOR STACKING	Height		Black			Internal				Finish
Open Out	Location							ASSEME	BLED*	** KIT FORM***
SASH	DESIGNS									SIDE FRAME
DV220 Square									_	Fixed
MIDRAIL/TRANSOM							1			DV118 Int Glazed
										Opener - Alitherm 400
Face None				•		-+	+			ETC4110 Outer
CILL						1	 			ETC4120 Ext.Glazed Sash ETC4129 Int. Glazed Sash
None							 			Coupler (Vertical)
85mm (ETC451) 150mm (ETC457)										SL075 Concealed to DV118 Only
190mm (ETC458)										UN3015 15mm*
225mm (ETC479)	'l			· · · · · · · · · · · · · · · · · · ·				.]		ETC357 25mm*
ADD-ON - 42mm UN3042 Head	Coupler (Horizontal Draine									Coupler (Horizontal Drained)
Cill Left	Door toplight, and side frames must be fabricated separately Min Sash Width 700mm NOTES								UN3000 (70 x 15mm)	
Right	Min Sash Width 700mm Max Sash Width 1200mm						Cill for full height sides			
Trickle Vents	Max Sash Height 2500mm As Bifold									
ADD-ON - 20mm	Restrictor 90°									Cill for flag side frames
	Not supplied as standard Required									None
Left										85mm (ETC451)
	French Door Handles							190mm (ETC457)		
HANDLE COLOUR	Master Aaster Aight									225mm (ETC479)
White	All French Door									ETC357 & UN3042 - when used together the Add-on is split and the
Silver Black	combinations will have double lever handles									coupler runs from cill to the top of the Add-on.
Grey										UN3015 & UN3042 - when used together the coupler will run to the underside of the Add-on, with Add-on
PREMIUM HANDLES		(TRANS		OVERALL SIZES TO					ILLS	running full width. Couplers are not structural, steel is recommended between bi-folds and
SS Ergonomic Lever	(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)								toplights.	
On Backplate	TERMS AND CONDITIONS Once the frames have been assembled, re-works, cut-downs and any alterations will not be possible. Please check the order requirements									
Toe and heeling kits supplied as standard.	carefully.									
Hinges, Rollers &	* Low Threshold has no weathering guarantee and is not recommended for external use. DV171 is used for Open In, DV271 for Open Out. ** Standard bifold glazing is 28mm Planitherm Total +, Argon, Black Thermobar, Toughened.									
Top Guides in Black	Black *** Doors exceeding 4000 in width or 2400 in height will be supplied in kit form. # Premium Handles will consist of Stainless Steel Ergonomic Lever and SS shootbolt handles on intermediate door.									
GLAZING **Glazed	# Premium Handles will co								ediate	door.
	All orders are subject to our terms and conditions of sale which are available at: www.a-w-s.co.uk									