



Customer		
Customer Address	Delivery Address (if different)	Page of
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

**OUTSIDE VIEW ONLY**

**LIST CODE**

**OUTER FRAME**

**VG510 Standard (99mm)**

**Cill**

- None
- 150mm (ETC457)
- 190mm (ETC458)
- 225mm (ETC479)
- Drainage (VG556)

**Add-on**

- 42mm (VG558) 
  - Head
  - Cill
  - Left
  - Right
- Trickle Vents?

**VG511 Upstand (116mm)**

**Cill**

- None
- 190mm (ETC458)
- 225mm (ETC479)

**Add-on**

- 42mm (VG572) 
  - Head
  - Cill
  - Left
  - Right
- Trickle Vents?

**INTERLOCKS**

**Standard 83mm**

- VG532 Reinforced In
- VG532 Reinforced Out

**Slim 35mm**

- VG536 Standard
- VG539 Reinforced Out

**HANDLE TYPE/COLOUR**

**D Handle**

- Inside Only/Half Cylinder

**Lever Handle**

- Inside Only/Half Cylinder
- Inside Lever/Fingerpull Out
- No External Locking

**Colour**

- White
- Silver Anodised
- Black

**PREMIUM HANDLES**

**Grey D Handle**

**Pole Handle (s/steel)**

- Both Sides
- Pole In/Fingerpull Out
- Half Cylinder Inside

**EXTRUSION COLOUR**

<b>External</b>	<b>Finish</b>
<b>Internal</b>	<b>Finish</b>
White Gloss (SA018E) <input type="checkbox"/>	
Grey Matt (RAL 7016) <input type="checkbox"/>	
Black Matt (RAL 9005) <input type="checkbox"/>	

**WIND LOADING** **MINIMUM 800PA**

Post Code	Altitude(m)
Distance to sea (Km)	
Exposed Location?	
Installation Height (Metres)	
PA	lx

**ITEM DETAILS**

Item	Qty
Location	
Width	
Height	
Assembled <input type="checkbox"/>	Kit Form <input type="checkbox"/>
Doc Q <input type="checkbox"/>	

**OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S**  
(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)

**GLAZING** (28mm GLAZING STANDARD)

Notes...

Planitherm Total + Argon, Thermobar  Unglazed  Other

**TERMS AND CONDITIONS**

Interlocks will be specified to meet wind loading requirements, please see the attached data sheet for further details.  
 Patio sashes slide on the inside as standard.  
 All patios are faced drained and must meet a minimum barrier rating of 800 PA.  
 Patio widths over 3000mm will be made in kit form as standard.  
 Patio outer frames exceeding 5000mm in width may require splitting. If not specified on the survey, we will split optimally.  
 Maximum sash height is 2500mm but must not exceed 250kg.  
 All sizes should be referred to in millimetres.  
 Glass units will be toughened as required for building regulations where necessary.  
 Doc Q comes glazed (Lami in/Tough Out) and a high security cylinder.

*All orders are subject to our terms and conditions of sale  
which are available at: [www.a-w-s.co.uk](http://www.a-w-s.co.uk)*