PLEASE CHECK CAREFULLY, ONCE SIGNED OFF WE ARE UNABLE TO ACCEPT AMENDMENTS AFFORDABLE ALUMINIUM SYSTEMS LTD VISOFOLD QUICK GLAZE CO-EX SURVEY

Customer			1				
Customer Address			Delivery Address (if different)			Pag	ge of
						God	ods
						VAT	-
						Tota	al
Contact			Delivery Method			Orc	ler Date
Tel			Despatch Route			Del	ivery Date
Fax			Customer Ref				
Email			Sales Contact				
OUTSIDE VI	EW ONLY				LIST CODE		
THRESHOLD	ITEM DETAILS	RUSION COLOUR					
Standard (50mm)	Item Qty	Whit	e Gloss (SA018E)				
Low* (15mm) Ramps (EUD03)	Width	Grey	Matt (RAL 7016)		External		Finish
DOOR STACKING	Height	Blac	k Matt (RAL 9005)		Internal		Finish
Open In	Location				DOC Q ASS	EMBLE	D*** KIT FORM***
Open Out	NOTES						
DV220 Square	110120						
MIDRAIL/TRANSOM							
DV235 109mm							
DRAINAGE Face None	OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S (TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)						
CILL	ITEM STYLE						
None 85mm (ETC451)			*				***
150mm (ETC457)						\vdash	M
190mm (ETC458) 225mm (ETC479)	**		***				***
ADD-ON - 42mm UN3042 Head						\leftarrow	M
Cill Left	M **	M	***	\leftarrow		$ \longrightarrow$	*
Right Trickle Vents	* [***				*
ADD-ON - 20mm						M#11.1	
— Cill — Left	*	+-	$ M\rangle$	wit	ternal locking not available h this style. ench Doors will have Lever	min 2 1280	ffic door No traffic door max min max 2486 2 1525 2523
Right Right				haı	ndles on both sashes	3 1870 4 2460 5 3075	3677 4889 4 2925 4925 6151
Chrome		 	* ***	wil	ench Doors within a bifold have Lever on Master and	6 3640 7 4230	
White				sho	potbolt on slave		w for DOC Q Guidelines
Silver Black Grey			*				
PREMIUM HANDLES							
SS Ergonomic Lever On Rose	TERMS AND CONDITIONS						
On Backplate	Once the frames have been assembled, re-works, cut-downs and any alterations will not be possible. Please check the order requirements carefully.						
Toe and heeling kits	Open In doors will have an ACDV274 'D' handle above each Debar handle. Black as standard. * Low Threshold has no weathering guarantee and is not recommended for external use. DV171 is used for Open In, DV271 for Open Out.						
supplied as standard. Hinges, Rollers &	** Standard bifold glazing is 28mm Planitherm Total +, Argon, Black Thermobar, Toughened.						
Top Guides in Black	*** Doors exceeding 4000 in width or 2400 in height will be supplied in kit form. # Premium Handles will consist of Stainless Steel Ergonomic Lever and SS shootbolt handles on intermediate door.						
GLAZING **Glazed	Doc Q comes glazed (6.8mm Lami in/Tough Out) and a high security cylinder. DOC Q must be within guidelines. Sash width between 700mm & 1200mm & max Sash height 2500mm.						
Unglazed Unglazed	All orders are subject to our	_		f sal	e which are available at: w	ww.a-w-:	s.co.uk