



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY

LIST CODE

DOOR

Open In Open Out

Full Swing

MASTER

Left

Right

OVERHEAD CLOSER

Hold Open

Non-Hold Open

HOOKLOCK

Number of locks

None

Full - Key in & Out

 ↳ Thumb In / Key Out

Half - Key in

 ↳ Thumb In

ELECTRIC STRIKE

12 Volt 24 Volt

AC DC

Fail Safe Fail Secure

Supplied with internal thumb turn & external override & upgraded latch

PAD HANDLE

None

White

Silver Anodised

Black

Powder Coated

CILL - DOOR

None 150mm (SH057)

CILL - SIDE PANEL / SCREEN

None 150mm (SH057)

THRESHOLD

Single SH413 Double SH410

GLAZING

Single 6.8mm Double 24mm

GLASS

Affordable Planitherm Total +

Unglazed

All orders are subject to our terms and conditions of sale which are available at www.A-W-S.co.uk

Customer Signature

Overall sizes to include cills and add-ons (transom, mullion and midrail sizes are excluding cills and add-ons)

EXTRUSION COLOUR

White Gloss (RAL9910G) Single Colour RAL/BS Matt (as standard)

Grey Matt (RAL 7016)

Black Matt (RAL 9005)

All items are:
800 PA

ITEM DETAILS

Item	Qty
Location	
Frame Width	
Frame Height	
Door Width	
Transom Drop	
Midrail Height	

Mullion Split

LEVER HANDLES & LATCH
Tokyo Handles & Nemeff Latch

Lockable

Non-Lockable (SA Only)

White

Silver Anodised

Black

PREMIUM HANDLES

D Handle 300mm, SSS, In & Out

 ↳ HAB20 Rounded

 ↳ HAB21 Offset

Pole Offset, SSS, In & Out

 ↳ 600mm

 ↳ 1200mm

 ↳ 1800mm

PANIC KIT

Single / Master Leaf

Slave Leaf

Paddle Handle

Ext Access Key & Fixed Pad

3080 Entry Trim Series

Please note: Commercial pivot doors do not have a weather rating. In exposed areas it is possible that they can be blown open, this can lead to draughts / water ingress. Consideration for additional weathering such as a canopy or porch should be made when carrying out site surveys.