PLEASE CHECK CAREFULLY, ONCE SIGNED OFF WE ARE UNABLE TO ACCEPT AMENDMENTS

AFFORDABLE ALUMINIUM SYSTEMS LTD					ALITHERM 400 DOOR SURVEY		
Customer							
Customer Address			Delivery Address (if different)		Page	of	
			G		Goods	oods	
				ľ	VAT		
					Total		
Contact					Order	Date	
Tel						ry Date	
Fax			Customer Ref			y Date	
Email			Sales Contact				
		LIST CODE					
Outer Frame - 70mm ETD410 Square	EXTRUSION COLOUR ##			CUSTOMER SIGNATURE		and an all the set	
Threshold		Colour	All orders are subject to our terms sale which are available at: ww				
Outerframe	Grey Matt (RAL 7016) Exte	ernal	MATT				
ETD495 Low Threshold	Black Matt (RAL 9005)	rnal					
Clip on extras for low thresh Not available on a cill.	Mullion Splits will be equal, unless noted Both Transoms are taken from the top of the frame. (TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDI					ILLS AND ADD-ON'S)	
EUD03 ramp In Out	ITEM DETAILS		1			All items are:	
Door Open In** ETD4204	Item Qty					800 PA	
Open Out ETD4205	Location						
	Width					Energy B	
Fixed Bead Square Only	Height		 			Side Frame 70mm	
Midrail	Midrail Height					DV118 (Int glazed)	
116mm Only	Ventilation (5000)					Opener - Alitherm 400	
Master Leaf	In Outer with 20mm Add-on					ETC4110 Outer	
Left Right	In 42mm Add-on					ETC4129 Int Glazed	
Add-On UN3020 (20mm)	Yes					ETC4120 Ext Glazed	
UN3042(42mm)	Colour		'			Transom/Mullion ETC4130 (57mm)	
Add-On Position	LIFT LEVER SECTION Cylinder Locking					ETC639 (109mm)	
Left Right	Full Cylinder -Key/Key	<u> ::</u>				Coupler (Vertical)	
Top	Anthra		s only available for 28mm & 2 ey & Black Only.	8.8mm Unit sizes, and in White,		UN3015 (70 x 15mm)	
Bottom	Half Cyl - Key In ## Qu Thumbturn In	ick Glaz	e not available on Coat to Or	der single colours.		Load Bearing (24mm)	
** Open in doors to be supplied with 20mm add-on down hinge	Furniture Colour					UN3015 coupler will be used unless ixx value	
side - unless coupled down hinge side, or noted otherwise	White					required is too great.	
Restrictor - Open Out	Silver Anodised					Coupler (Horizontal Drained)	
Supplied as standard X	Chrome Black					Cill for full height sides	
DRAINAGE Face	Grey					None	
	PREMIUM (SSS only)					As Door	
None	Ergonomic Lever					Cill for flag side frames	
85mm (ETC451)	Lever on Rose					None	
150mm (ETC457) 190mm (ETC458)	SLAM LOCK SECTION Cylinder Locking					85mm (ETC451)	
225mm (ETC479)	Full Cylinder -Key/Key					190mm (ETC457)	
Hinge Colour	Thumbturn / Key					225mm (ETC479)	
White	AV4 with magnet					ETC357 & UN3042 - when	
Black Grey	& daylatch					used together the Add-on is split and the coupler runs from cill to the top of the	
Glazing	Offset, SSS, In & Out					Add-on. UN3015 & UN3042 - when	
Glazed Planitherm Total+ Argon	fixed through the sash 600mm					used together the coupler will run to the underside of the	
	1200mm					Add-on, with Add-on running full width.	
					100	Couplers are not structural.	