



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY

LIST CODE

OUTER FRAME

006.1900 - 1 Slider (139mm)

006.1901 - 2 Sliders (139mm)

INTERLOCKS

Slim - 50mm (006.2230)*

Standard - 94mm (006.1986)

EXTRUSION COLOUR

External	Finish
Internal	Finish
White Gloss <input type="checkbox"/>	
Grey Matt (7016M) <input type="checkbox"/>	
Black Matt (9005) <input type="checkbox"/>	

WIND LOADING **MINIMUM 800PA**

Post Code	Altitude (metres)
Distance to Sea (Km)	
Exposed Location?	
Installation Height (metres)	
PA	lx

REINFORCING (50mm Only)

0090/0091 In (30mm Only)

Out (30mm Only)

Both Sides (60mm)

0092/0093 In (50mm Only)

Out (50mm Only)

Both Sides (100mm)

ITEM DETAILS

Item	Qty	
Location		
Width		
Height		
Kit Form <input checked="" type="checkbox"/>		

HANDLE TYPE

Lever Handles

In & Out (Locking In & Out) STD

Inside Only (No External Locking)

Inside Lever/Fingerpull Out (No External Locking)

HANDLE COLOUR

White

Silver (Painted RAL7040)

Black

Anthracite Grey

PREMIUM HANDLE

Stainless Steel

*Slim not available on this design Handles inside only

*Slim not available on this design Handles inside only

This design uses 006.1900 Outerframe

* Meeting stile = Standard 94mm Sashes

Handles both sides, dependant on windloading (MAX ixx48).
If 030.1099 reinforcing required, then locking is internal only.

OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S
(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)

REINFORCING (94mm only)

3097/1096 In (37mm)

Out (37mm)

Both Sides (74mm)

3099/1097 In (60mm)

Out (60mm)

Both Sides (120mm)

3099/1098 In (60mm)

Out (60mm)

Both Sides (120mm)

ADD ON'S - 39mm (015.0183)

Head

Cill

Left

Right

Trickle Vents

FIXING LUGS (056.6020)

THRESHOLD (Supplied As Standard)

DO NOT FIX THROUGH THE THRESHOLD

CILL PRESSING

DO NOT FIX THROUGH THE THRESHOLD

RP110 110 x 36

UTL036 60 x 40

UTL035 50 x 30

CILL

ETC458 190mm Supplied with thermal break tape

No Cill / Pressing Required

GLAZING (28mm Standard)

Planitherm Total + Argon, Thermobar

Unglazed

Other (Specify in Notes)

NOTES

TERMS AND CONDITIONS / EXTRA INFO

- Interlocks will be specified to meet windloading requirements, if reinforcing is required then it will be to the outside.
- Patio sashes slide on the inside as standard.
- All patios are faced drained and must meet a minimum barrier rating of 800PA.
- Patio outer frames exceeding 5000mm in width may require splitting. If not specified on the survey, we will split optimally.
- Maximum sloping pressing length is 3000mm. Anything exceeding this will be split with a butt strap.
- Maximum sash height is 2700mm, maximum sash width is 2700mm but must not exceed 300kg.
- All sizes should be referred to in millimetres.
- On dual colour orders with white inside, the inside of the patio and the inside of the cill may have a slight variance in colour.

All orders are subject to our terms and conditions of sale which are available at: www.a-w-s.co.uk