



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY

LIST CODE

OUTER FRAME

Triple Track (210mm)

INTERLOCKS

Standard 94mm (006.1986)

Slim not available on triple track

REINFORCING

3097/1096 Out (37mm)

3099/1097 Out (60mm)

3099/1098 Out (60mm)

39mm ADD ONS (015.0183)

Head

Cill

Left

Right

Trickle Vents

FIXING LUGS (056.6020)

THRESHOLD

(Supplied as standard)

DO NOT FIX THROUGH THE THRESHOLD

NO CILL

NO CILL AVAILABLE

CILL PRESSING

DO NOT FIX THROUGH THE THRESHOLD

RP110 110 x 36

UTL036 60 x 40

UTL035 50 x 30

No Cill/Pressing Required

GLAZING (28mm Standard)

Planitherm

Total + Argon, Thermobar

Unglazed

Other (Specify in Notes)

Max Glazing uses 43mm bead. Gaskets adjusted to suit actual glazing thickness?

EXTRUSION COLOUR

External	Finish
Internal	Finish
White Gloss <input type="checkbox"/>	
Grey Matt (7016M) <input type="checkbox"/>	
Black Matt (9005) <input type="checkbox"/>	

WIND LOADING **MINIMUM 800PA**

Post Code _____ Altitude (M) _____

Distance to Sea (Km) _____

Exposed Location?

Installation Height (M) _____

PA _____ lx _____

ITEM DETAILS

Item	Qty
Location	
Width	
Height	
Kit Form <input checked="" type="checkbox"/>	

HANDLE TYPE

Lever Handles

In & Out (Locking In & Out) STD

Inside Only (No External Locking)

Inside Lever/Fingerpull Out (No External Locking)

HANDLE COLOUR

White

Silver (Painted RAL7040)

Black

Anthracite Grey

PREMIUM HANDLE

Stainless Steel

* Meeting stile = Standard 94mm Sashes

Handles both sides, dependant on windloading (MAX ixx48). If 030.1099 reinforcing required, then locking is internal only.

OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S
(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)

NOTES

TERMS AND CONDITIONS / EXTRA INFO

- Interlocks to meet windloading requirements, if reinforcing is required then it will be to the outside as standard.
- Patio sashes slide on the inside as standard.
- All patios are faced drained and must meet a minimum barrier rating of 800PA.
- Patio outer frames exceeding 5000mm in width may require splitting. If not specified on the survey, we will split optimally.
- Maximum sloping pressing length is 3000mm. Anything exceeding this will be split with a butt strap.
- Maximum sash height is 2700mm, maximum sash width is 2700mm but must not exceed 300kg.
- All sizes should be referred to in millimetres.
- On dual colour orders with white inside, the inside of the patio and the inside of the cill may have a slight variance in colour.

All orders are subject to our terms and conditions of sale which are available at: www.a-w-s.co.uk