PLEASE CHECK CAREFULLY, ONCE SIGNED OFF WE ARE UNABLE TO ACCEPT AMENDMENTS AFFORDABLE ALUMINIUM SYSTEMS LTD VISOFOLD QUICK GLAZE CO-EX SURVEY

Customer							
Customer Address	Delivery A	Delivery Address (if different)			Page of		
						Goods	
						VAT	
						Total	
Contact		Delivery N	lethod			Order Date	
Tel		Despatch	Route			Delivery Dat	e
Fax		Customer	Ref				
Email		Sales Con	tact				
OUTSIDE VI	EW ONLY			LIST C	ODE		
THRESHOLD	ITEM DETAILS	EXTRUSION CO	DLOUR ##	ŧ			
Standard (50mm) Low* (15mm)	Item Qty	White Gloss (SA0	18E)				
Ramps (EUD03)	Width	Grey Matt (RAL 7	016)	External		Finish	ı
DOOR STACKING	Height	Black Matt (RAL 9	0005)	Internal		Finish	i
Open In Open Out	Location			DOC Q	ASSEME	BLED***	KIT FORM***
SASH	NOTES						
DV220 Square							
DV235							
DRAINAGE Face None	OVERALL SIZES TO INCLUDE CILLS	& ADD-ON'S (TRANS	OM, MULLIC	N & MIDRAIL MEASUREMEN	ITS ARE EX	CLUDING CILLS	AND ADD-ON'S)
CILL	ITEM STYLE						
None 85mm (ETC451) 150mm (ETC457)		*			\leftarrow	M	***
190mm (ETC458) 225mm (ETC479) ADD-ON - 42mm	M → **	***	\leftarrow		\leftarrow	M	***
UN3042 Head Cill Left Right	M **	M →→ ***	\leftarrow			\rightarrow	*
Trickle Vents ADD-ON - 20mm	*	***	\leftarrow		\leftarrow		*
Head Cill Cill Right	*	***	wit ** Fre	ternal locking not availa th this style. ench Doors will have Le	ible ever 3	ith traffic door min max 1280 2486 1870 3677	No traffic door min max 2 1525 2523
HANDLE COLOUR Chrome White		*	*** Fre	ndles on both sashes ench Doors within a bifo I have Lever on Master ootbolt on slave	old 5 and 6 7	2460 4889 3075 6151 3640 7290 4230 8480 below for DOC	4 2925 4925 6 4330 7320 Q Guidelines
Silver Black Grey		*					
PREMIUM HANDLES SS Ergonomic Lever	TERMS AND CONDITIONS						
On Rose	Once the frames have been assembled, re-works, cut-downs and any alterations will not be possible. Please check the order						
On Backplate	requirements carefully. Open In doors will have an ACDV274 'D' handle above each Debar handle. Black as standard.						
Toe and heeling kits supplied as standard.	* Low Threshold has no weathering guarantee and is not recommended for external use. DV171 is used for Open In, DV271 for Open Out. ** Standard bifold glazing is 28mm Planitherm Total +, Argon, Black Thermobar, Toughened.						
Hinges, Rollers & Top Guides in Black	*** Doors exceeding 4000 in width or 2400 in height will be supplied in kit form. # Premium Handles will consist of Stainless Steel Ergonomic Lever and SS shootbolt handles on intermediate door. Doc Q comes glazed (6.8mm Lami in/Tough Out) and a high security cylinder. DOC Q must be within guidelines. Sash width between						
**Glazed	700mm & 1200mm & max Sash height 2500mm. ## Quick Glaze not available on Coat to Order single colours.						
Unglazed	All orders are subject to our terms and conditions of sale which are available at: www.a-w-s.co.uk						